



A  
MALE

B  
FEMALE

REVISIONS		
REV	DESCRIPTION	APPROVED

PIN		OUTS	
A	B	A	B
DB 25 MALE	DB 9 FEMALE	DB 25 MALE	DB 9 FEMALE
8	1	1	1
3	2	2	2
2	3	3	3
20	4	4	4
7	5	5	5
6	6	6	6
4	7	7	7
5	8	8	8
22	9	9	9
Shell	Shell	Shell	Shell

NOTES:

- 1.MOLDED CONNECTOR END REQUIREMENTS:
- A.INNER MOLD USING PE
- B.ALUMINUM FOIL WRAP TO CONNECTOR
- C.PVC - 45P PLATINUM GRAY

INSULATION: UPON 1M ohm AND 1M ohm ELECTRIC CONDUCTION:INSIDE 1.5K ohm			
5	(SCREW)NUT:4.75*6mm NICKEL-PLATING	2PCS	
4	THUMBSCREW: MALE 4*22mm NICKEL-PLATING	4PCS	
3	CONNECTOR:DB25P MALE NICKEL-PLATING, INSULATOR COLOR:BLUE	1PCS	
2	CONNECTOR:DB9P FEMALE NICKEL-PLATING, INSULATOR COLOR:BLUE	1PCS	
1	CABLE:JUMPER 26AWG OR 28AWG	10PCS	
ITEMNO	PART NAMES	QTY	REMARK

	PRODUCT	DB9P FEMALE TO DB25P MALE ADAPTER	CUSTOMER		DRAWN	Hvon .w	 THREE ANGLE PROJECTION
	CUS,NO	309	VERSION		CHECKED	Jackson Cang	
	DR,NO	SD309	DRAWN DATE	OCT.10,2000	APPROVERD	Jonny Chuang	