

2 Input to 1 Output HDMI Switch GXHD-21



Features:

- Switch easily between any two HDMI sources automatically
- Maintains high resolution video-beautiful, sharp HDTV resolutions up to 1080p,2k,1440p graphics and computer resolutions up to 1920 x 1200 are easily achieved.
- No external power needed
- Up to 24 bit color depth.
- Up to DTS Master Audio and Dolby Digital True HD Support
- HDMI pass-through
- HDCP pass-through
- Compatible with HDMI1.3 devices.

Specifications:

- Operating temperature range.....-5 to 35 °C (-41 to 95 °F)
- Operating humidity range.....5 to 90% RH (no condensation)
- Video Amplifier Bandwidth.....140 MHz
- Input Video Signal.....0.5-1.0 volts p-p
- Input DDC Signal.....5 volts p-p (TTL)
- Maximum Single Link Range.....1280 x 1024, 1080p
- Video format supported:
- VGA:.....640x480,800x600,1024x768,1280x1024
- DTV/HDTV:.....480i/576i/480p/576p/720p/1080i/1080p
- Output Video.....HDMI1.3+HDCP1.0/1.1
- Vertical Frequency Range:.....60Hz
- Power Consumption.....10 Watts (max.)
- Dimensions.....85mmW x 15mmH x 43mmD
- Weight.....80gs

© Copyright 2007 Jo-Dan International, Inc. all rights reserved. Plus Series®, PowerCore®, QuickConnect®, Share Plus®, and GoldX® Products are registered trademarks of Jo-Dan International, Inc. All other trademarks and registered trademarks are the property of their respective owners. Designed in USA. Made in China. One or more of the following patents may apply: D494,935, D494,934, D494,932, D493,453, 6,755,676, D490,702, 6,736,658, 6,726,509, 6,716,047, D485,752, D484,044, D481,629, D481,628, 6,607,408, D478,001, D478,000, D468,635, 6,479,607, D465,223,6,454,584, D462,612, D452,427, D452,426, D451,888, D451,480, D450,303, D448,736, D444,772, D443,862, D443,593, D442,919, D442,556, D442,555, 5,788,521, 5,658,158, 5,334,033, 5,292,257, D503,882; 6,843,684; 6,854,989; 6,872,086; D506,386; 6,905,374; D509,797; 6,991,483; D513,976; 7,004,787; 7,028,114; D519,925; D522,507; 7,258,572. Other patents pending.