



NOTES:

1. CABLE:[28AWG(7/0.127) * 1P+24AWG(7/0.203)*2C+ AL/MY+DW(7/0.127)+65%BD(16/5/0.1)]TIN INSULATION WIRE ONE:FO-PE,OD= ϕ 0.84 \pm 0.03MM COLOR: WHITE&GREEN INSULATION WIRE TWO:SR-PVC,OD= ϕ 1.1 \pm 0.05MM COLOR:BLACK,RED JACKET:80°C 80P PVC OD= ϕ 5.00 \pm 0.10MM FINISHED PRODUCTS LENGTH:
(1) LENGTH=6FT TOLERANCE: \pm 25.4mm

PIN OUTS		
DB 9P M+PCB(P1)	WIRE COLOR	USB A M(P2)
1	RED	1
4	BLACK	4
2	WHITE	2
3	GREEN	3
SHELL		SHELL

INSULATION: UPON 1M ohm AND 1M ohm ELECTRIC CONDUCTION:INSIDE 1.5K ohm			
5	BLACK SHELL PRINTING "GOLDX" ONLY "GOLD" IS GOLD THE OTHERS' COLOR IS WHITE.	1SET	
4	THUMBSCREW: 4*66mm PLATE WITH GOLD , COLOR : PANTONE#322C 45P PVC	2PCS	
3	CONNECTOR: USB AM , PIN : G/F , COLOR : PANTONE#426C 45P PVC. (871C) "X" ON BOTH SIDES.	1PCS	
2	CONNECTOR: DB 9P M ,INSULATOR COLOR: PANTONE#322C	1PCS	
1	CABLE: 1P 28AWG; 2C 24AWG, JACKET:TRANSLUCENT-YELLOW WITH GOLD PARTICLES.	1PCS	
ITEM NO	PART NAMES	QTY	REMARK



PRODUCT	USB AM TO PCB	CUSTOMER	GOLDX	DRAWN	
CUS,NO	GXMU-1200	VERSION	1	CHECKED	DJ
DR,NO	SDGXMU-1200	DRAWN DATE	JULY.26.2002	APPROVERD	JACKY

