

8-OUTLET SURGE PROTECTOR GXS-712MC

You can stop destructive surges from crippling you hardware and scrambling software data with a GoldX® surge protector. This product is designed to detect and dissipate damaging power surges before they harm your electronic equipment fax/modem line protection



Features:

- Dual coax line protection
- 8 grounded power outlets
- Surge protection LED indicator
- Ground LED indicator
- Surge protection alarm with auto current shut off
- EMI/RFI noise filtering
- Illuminated on/off switch
- Extra space for AC adapters

Protect your Computer Systems from:

- System crashes
- Corrupted data files
- Power disturbances
- Disk drive errors
- Hardware damage

TECHNICAL SPECIFICATIONS

ELECTRICAL RATING:

125 V, 15 A, 60 Hz, 1875 Watts

SURGE PROTECTION PERFORMANCE:

UL Clamping Voltage	330V (H-N, H-G, N-G)
Maximum Energy Displacement	2280 Joules
Maximum Current	27000 A
Maximum Spike Voltage	6500 V
Response Time	< 1 Nanosecond

EMI/RFI NOISE FILTER:

Frequency Range	100 KHz - 50 MHz
Attenuation	4 to 52 dB

FAX/MODEM PROTECTION PERFORMANCE:

UL Clamping Voltage	400 V
Maximum Energy Displacement	106 Joules

COAXIAL PROTECTION PERFORMANCE:

UL Clamping Voltage	140 V
Maximum Current	500 A

\$75,000 Connected Equipment Warranty:

If, during the time period listed for you model, any equipment properly connected to the Surge Protector is damaged by a transient spike or surge (as defined by industry standards) that enters the equipment through a properly installed Gold® surge protector, Jo-Dan International (JDI) will reimburse your reasonable cost to repair or replace the damaged equipment (at the option of JDI) up to the maximum U.S. dollar amount listed for your specific surge protector. Please see the installation guide for your model for additional details.