


Drawing Number: P6-003-□□□□□


- Housing Material: Polycarbonate, UL Flammability Rating:
 - ①=UL 94V-0, RoHS Compliant.
 - ②=UL 94V-2, RoHS Compliant.
- Contacts Type:
 - ①=Straight pin fits Stranded wire only.
 - ②=Two prong angled pin fits Solid/Stranded Wires.
 - ③=Three prong pin fits Solid/Stranded Wires.
- Gold Plating:
 - ⓕ= Fu" (Flash), ⓐ=2-3u" ($0.0508 \mu m \leq A \leq 0.0762 \mu m$),
 - ⓗ= 3u" ($\geq 0.0762 \mu m$), ⓑ= 6u" ($\geq 0.1524 \mu m$),
 - ⓒ=15u" ($\geq 0.381 \mu m$), ⓓ=30u" ($\geq 0.762 \mu m$),
 - ⓔ=50u" ($\geq 1.27 \mu m$).
- Packaging Quantity:
 - Ⓢ=1000pcs, Ⓣ=500pcs, Ⓤ=250pcs, Ⓥ=200pcs
 - Ⓦ= 100pcs, Ⓧ= 50pcs, Ⓨ= 25pcs, Ⓩ= 10pcs
 - ⓐ= Other
- Housing Color: Transparent, other colors are available.
(Red=RD, Orange=OR, Yellow=YL, Green=GN, Blue=BL, Purple=PU, Black=BK)
- Shielded Material: Brass with nickel plated, or Non-Shielded.
- Operating Temperature: -10°C to 60°C.

NO: PX-0XX-□□□□□

- Housing Material (0, 2)
- Contacts type (1, 2, 3)
- Gold plating (F, A, H, B, C, D, E)
- Packaging Quantity (S, T, U, V, W, X, Y, Z)
- Housing Color (RD, OR, YL, GN, BL, PU, BK)



NOTE TOL: ±0.1

| | | | | | | | | | | |
|-----|---------------------------------|-------|-----|----------|-------|------|------------|---------------|------|---|
| B | 2017.09.28. Rescheduling coding | 3RD | ⊕ | Drawing | Chidy | Date | 2004/11/11 | UL Code | 6P4C |  |
| A | An initial version | Unit | m/m | Checked | Chris | Date | 2004/11/11 | Description | | |
| Rev | Description | Scale | 1:1 | Approved | Jason | Date | 2004/11/11 | AC-6P4C-F-100 | | |