



Drawing Number: P6-001-□□□□□

- Housing Material: Polycarbonate, UL Flammability Rating:
 - ①=UL 94V-0, RoHS Compliant.
 - ②=UL 94V-2, RoHS Compliant.
- Contacts Type:
 - ①=Straight pin fits Stranded wire only.
 - ②=Two prong angled pin fits Solid/Stranded Wires.
 - ③=Three prong pin fits Solid/Stranded Wires.
- Gold Plating:
 - Ⓕ= Fu" (Flash), Ⓖ= 2-3u" ($0.0508 \mu m \leq A \leq 0.0762 \mu m$),
 - Ⓖ= 3u" ($\geq 0.0762 \mu m$), Ⓒ= 6u" ($\geq 0.1524 \mu m$),
 - Ⓒ= 15u" ($\geq 0.381 \mu m$), Ⓓ= 30u" ($\geq 0.762 \mu m$),
 - Ⓔ= 50u" ($\geq 1.27 \mu m$).
- Packaging Quantity:
 - Ⓢ=1000pcs, Ⓣ=500pcs, Ⓤ=250pcs, Ⓟ=200pcs
 - Ⓠ= 100pcs, Ⓡ= 50pcs, Ⓢ= 25pcs, Ⓣ= 10pcs
 - Ⓤ= Other
- Housing Color: Transparent
- Shielded Material : Brass with nickel plated, or Non-Shielded.
- Operating Temperature: -10°C to 60°C.

NOTE TOL: ±0.1

B	2017.09.28. Rescheduling coding	3RD		Drawing	<i>Chidy</i>	Date	2004/11/11	UL Code	6P6C	
A	An initial version	Unit	m/m	Checked	<i>Chris</i>	Date	2004/11/11	Description		
Rev	Description	Scale	1:1	Approved	<i>Jason</i>	Date	2004/11/11	AC-6P6C-F-100		