



Part Number	Inner Diameter (P) mm	Outer Diameter (D) mm	Pitch (W) mm	Wrapping Range Min mm	Wrapping Range Max mm
SW-018P	1.5	3	4	1.5	10
SW-014P	4	6	7	4	50
SW-038P	7.5	10	11.4	7.5	60
SW-012P	9	12	13.9	9	65
SW-034P	15	19	18.2	15	100
SW-100P	20	24	19.6	20	130
SW-125P	26	30	43	26	150

Part Number	Inner Diameter (P) in	Outer Diameter (D) in	Pitch (W) in	Wrapping Range Min in	Wrapping Range Max in
SW-018P	0.06	0.12	0.16	0.06	0.39
SW-014P	0.16	0.24	0.28	0.16	1.97
SW-038P	0.30	0.39	0.45	0.30	2.36
SW-012P	0.35	0.47	0.55	0.35	2.56
SW-034P	0.59	0.75	0.72	0.59	3.94
SW-100P	0.79	0.94	0.77	0.79	5.12
SW-125P	1.02	1.18	1.69	1.02	5.91

Material: Constructed from Polyethylene (PE).

Usage Instructions: Secure one end using a releasable cable tie initially, followed by wrapping the wires in a clockwise direction to ensure they are tightly bound.

Application: Serves as a protective covering for electrical wires, providing both insulation and an aesthetically pleasing appearance.

SW-

Spiral Wrap

unit: mm