



Connecting List:

| P1 | | P2 | |
|-------|-------|-------|--|
| 1 | Red | 1 | |
| 2 | Green | 2 | |
| 3 | White | 3 | |
| 4 | Black | 5 | |
| Shell | | Shell | |

Inspection And Testing:

- Product must be 100% tested 4 times:
 - No short;
 - No Open Circuit;
 - No Dislocation.
- Electronics Testing:
 - Insulation Resistance:10MΩ
 - Conductor Resistance:5Ω
 - Voltage Rating:300V

Material List:

| Item | Part | Specifications | Unit | Q'TY |
|------|--------------|-------------------------------------------|------|------|
| 1 | Cable | 28AWG*1P+28AWG*2C+AL+D, OD:3.8mm,Black | PCS | 1 |
| 2 | Connector | Micro USB B Male,Black | PCS | 1 |
| 3 | Connector | USB A Male,Black | PCS | 1 |
| 4 | InnerMolding | LDPE Transparent | Gram | |
| 5 | OuterMolding | 45P Black PVC | Gram | |

| PART | CABLE LENGTH±TMM |
|------------|------------------|
| U2-AAMM-01 | 457.5±20mm |
| U2-AAMM-06 | 1830±20mm |

| | |
|----------------|---------------|
| Customer No: | |
| Customer Name: | |
| Product Name: | |
| Packing: | PE Bag/One PC |



| | | | |
|-------------|----------------------|-----------------|-------------|
| | Proportion: 2.5:1 | Edition: A/1 | Drawing By: |
| | Unit:MM | | Confirm: |
| Drawing No: | Data: 2017.12.13 | Approval: | |