


Scale: mm

1 Meter (3.28 FT) High Speed HDMI to Micro HDMI D Cable with Ethernet

VIVID AV®



CABLE CONSTRUCTION

Mode1	L (mm)
AV-HDMIAD-001M	1000±30
AV-HDMIAD-002M	2000±50
AV-HDMIAD-003M	3000±50

		CONDUCTOR: 1/0. 2BC*1P
	X	INSULATION: FPE
		DRAIN: 1/0. 2BC
		AL FOIL
		CONDUCTOR: 1/0. 2BC
	0	INSULATION: PE
		—— DRAIN: 1/0. 2BC
		AL FOIL
	" —	JACKET:PVC
22		

		1 3 5 5	10 12
		4 6 8	13 — 15 —
Connector A	HDMI AMale	2 - 4	16
Connector B	HDMI D Male	7 AX 9	18 —
Color	Black	9 11 13	19
<i>N</i> arranty	Lifetime Warranty	SHELL DRAIN SHELL	17
RoHS Compliant	Yes	Features:	
	^ FT	i catules.	

Length 3FT Weight (Lbs) 0.09



RoHS compliant TV Test: Standards: 4K (3840x2160) 60Hz 1M, 2M 4K (3840x2160) 30Hz 3M

PIN OUT